




IDRAPOINT

IDRAULICA ONLINE

ca, lunga



Campi di applicazione

- Per l'evacuazione delle acque reflue nere e bianche

Dati tecnici


Materiale	PE-HD
-----------	-------

Caratteristiche

- Resistente ai raggi UV

Art. no.	d, Ø [mm]	d1, Ø [mm]	A [cm]	L [cm]	I1 [cm]	I2 [cm]	K1 [cm]	K2 [cm]	SU4 [pz.]	SU3 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
368.584.16.1	125	110	0,7	16	7	6,4	4	3	200	50	10	1	11,28
369.584.16.1	160	110	2,5	28	9,4	6,4	6	3	96		12	1	60,26
369.587.16.1	160	125	1,7	24	9,4	8	6	5	120		10	1	60,26
370.584.16.5	200	110	4,3	28	11,5	3,7	4	0			5	1	70,76
370.587.16.5	200	125	3,6	28	11,5	3,7	4	0			10	1	70,76
370.594.16.5	200	160	2	28	11,9	9,1	4	6			5	1	70,76
371.596.16.1	250	200	2,5	40,5	15,8	15,7	8	8			5	1	107,84
372.596.16.1	315	200	5,7	58	16,1	15,7	8	8				1	145,77
372.598.16.1	315	250	3,2	43,5	16,1	15,7	8	8				1	145,77

Riduzione Geberit PE concentrica, corta



Campi di applicazione

- Per l'evacuazione delle acque reflue nere e bianche

Dati tecnici

Materiale	PE-HD
-----------	-------

Caratteristiche

- Resistente ai raggi UV

Art. no.	d, Ø [mm]	d1, Ø [mm]	H [cm]	h [cm]	K [cm]	SU4 [pz.]	SU3 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
360.557.16.1	40	32	8	3	1,5		100	10		1,16
361.557.16.1	50	32	8	3	1,5		100	10	1	1,16
361.559.16.1	50	40	8	3	1,5	2000	50	10		1,16
363.559.16.1	56	40	8	3	1,5		80	10	1	1,72
363.560.16.1	56	50	8	3	1,5	1200	50	10	1	1,79
364.559.16.1	63	40	8	3	1,5			10	1	1,55
364.560.16.1	63	50	8	3	1,5		50	10	1	1,55