


Tubi

Tubo Geberit PE



Campi di applicazione

- Per l'evacuazione delle acque reflue nere e bianche

Dati tecnici

Materiale	PE-HD
-----------	-------

Caratteristiche


- Resistente ai raggi UV

Art. no.	d, Ø [mm]	di, Ø [mm]	s [mm]	L [m]	A ² [cm ²]	PN [bar]	S	SU4 [m]	SU2 [m]	EUR/m
379.000.16.0	32	26	3	5	5,3	10,3	5	590	5	2,40
360.000.16.0	40	34	3	5	9	8,1	6,3	415	5	2,98
361.000.16.0	50	44	3	5	15,2	6,4	8	540	5	3,76
364.000.16.0	63	57	3	5	25,4	5	10	250	5	5,00
365.000.16.0	75	69	3	5	37,3	4,1	12,5	510	5	5,90
366.000.16.0	90	83	3,5	5	54,1	4	12,5	405	5	8,09
367.000.16.0	110	101,4	4,3	5	80,7	4	12,5	475	5	12,04
368.000.16.0	125	115,2	4,9	5	104,5	4	12,5	385	5	16,18
369.000.16.0	160	147,6	6,2	5	171,1	4	12,5	195	5	26,26
370.000.16.0	200	187,6	6,2	5	276,4	3,2	16	70	5	33,09
371.000.16.0	250	234,4	7,8	5	431,5	3,2	16	55	5	51,66
372.000.16.0	315	295,4	9,8	5	685,3	3,2	16	40	5	81,88

Raccordi

Curve

Curva Geberit PE



Campi di applicazione

- Per l'evacuazione delle acque reflue nere e bianche

Dati tecnici


Materiale	PE-HD
-----------	-------

Caratteristiche

- Resistente ai raggi UV

Art. no.	d, Ø [mm]	X [cm]	K [cm]	SU4 [pz.]	SU3 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
arc / Angolo: 45°								
360.045.16.1	40	4	2	2400	100	10		1,79
361.045.16.1	50	4,5	2	1600	100	10		2,00
364.045.16.1	63	5	2	1040	260	10		3,21
365.045.16.1	75	5	2	800	50	10		5,15
366.045.16.1	90	5,5	2	480	30	10		7,82
367.045.16.1	110	6	2,5	280	70	10		8,13
368.045.16.1	125	6,5	2,5	200	50	10	1	12,04
369.045.16.1	160	6,9	2	120	10		1	32,23
370.045.16.1	200	18	2,5	28	7		1	62,11
arc / Angolo: 88,5°								
361.088.16.1	50	6	2	1200	50	10		2,00
364.088.16.1	63	7	2	800	200	10	1	3,21
365.088.16.1	75	7,5	2	480	30	10	1	5,15
366.088.16.1	90	8	2	320	80	10		7,82
367.088.16.1	110	9,5	2,5	200	50	10		8,13
368.088.16.1	125	10	2,5	160	40	10	1	12,04
369.088.16.1	160	12	2,5	72	6		1	32,23

Curva Geberit PE a gambo lungo



Campi di applicazione

- Per l'evacuazione delle acque reflue nere e bianche

Dati tecnici

Materiale	PE-HD
-----------	-------

Caratteristiche

- Resistente ai raggi UV

Art. no.	d, Ø [mm]	X1 [cm]	X2 [cm]	K1 [cm]	K2 [cm]	r [cm]	SU4 [pz.]	SU3 [pz.]	SU2 [pz.]	SU1 [pz.]	EUR/pz.
arc / Angolo: 45°											
367.046.16.1	110	14,7	6	11	2,5	–	160	40	10	1	12,80

